




- 开启角度: 105度
- 铰杯厚度: 10.5毫米
- 铰杯直径: 35毫米
- 面板(K)尺寸: 3毫米-7毫米
- 材质: 铁镀镍
- 门可选用板厚: 14毫米-20毫米
- Opening angle: 105°
- Depth of hinge cup: 10.5mm
- Diameter of hinge cup: 35mm
- Drilling distance on the door(K): 3-7mm
- Material: cold rolled steel, nickel plated
- Range of door thickness: 14-20mm


F05系列内置阻尼自动铰链功能图 F05 Installation dimensions

D: 盖位计算值表 Overlay
A: 间隙位计算值表 Gap



F05A 全盖 Full overlay

$$H=14+K-D$$




H \ D \ K	K				
	3	4	5	6	7
0	17	18	19	20	21
2	15	16	17	18	19
4	13	14	15	16	17



F05B 半盖 Half overlay

$$H=5+K-D$$




H \ D \ K	K				
	3	4	5	6	7
0	8	9	10	11	12
2	6	7	8	9	10
4	4	5	6	7	8




F05C 内嵌 Insert

$$H=-4+K+A$$



H \ A \ K	K				
	3	4	5	6	7
0	1	0	-1	-2	-3
2	3	2	1	0	-1
4	5	4	3	2	1

铰杯种类 Hinge cup types



可配底座 Plate

序号 No	名称 Item no.	H值 H Value	孔型/安装尺寸L Hole type/Mounting dimension	类型 type
1	F40T	H=0	四孔 four holes/37mm	普通 Normal
2	F10S/F12S/F14S	H=0/2/4	两孔 two holes/37mm	普通 Normal
3	F40S/F42S/F44S	H=0/2/4	四孔 four holes/37mm	普通 Normal

安装尺寸L(Mounting dimension L)

安装尺寸L(Mounting dimension L)

侧板边沿 Side board edge

侧板边沿 Side board edge

